




# mex+1417WGC/WCC

Wireless most versatile DR flat panel

- WIFI Complete Wireless solution
- AED Automatic Exposure Detection (no triggering needed)
- WATER-RESISTANT Protection against water impact (IPX6)
- AP (ACCESS POINT) MODE Direct Wi-Fi communication between detector and workstation
- OLED Display Indication of panel, connection and battery status
- CASSETTE SIZE Ultra thin 36cm x 43cm Retrofit Solution
- UNIVERSAL Suitable for mobile and stationary use
- SUPERIOR IMAGE QUALITY Due to  $127 \mu m$  and 3,9 line pairs / mm

### Application possibilities meX+1417WGC / WCC





#### **Batteries & Charger**



- Battery Type: Lithium Ion
- Charging Time: Typ. 3 hrs
- Operation Time: 4 hrs / 960 images (@cycle time = 15 sec.)

## As table solution due to ultra flat cassette size






### meX+ Image Acquisition Software

- Simple and perfect images at all time
- Integrated automatic image optimization
- Touchscreen function for easy operating
- Fully integrated radiographic positioning guide
- Bones and soft tissue in one image
- Including Patient CD and DICOM Send function
- Adaption of almost every language possible
- Modern graphical user interface
- Safe and fast registration of emergency patients
- Entry of recurring examination procedures as macros

### Dimensions





### Specifications

Data Interface	Wireless
Sensor Type	Amorphous Silicon with TFT
Dimensions	384 x 460 x 15 mm
Active Area	358 x 423 mm
Scintillator	Gadolinium Oxysulfide (Gadox) or Cesium-lodide (Csl)
Weight	3 kg
Pixel number	2756 x 3268 pixels
Pixel pitch	127 μm
Limiting Resolution	3,9lp / mm
A/D Conversion	14/16 bit
Energy Range	40 - 150 kV
Data Acquisition Time	5,0 sec.

Distributor



Im Erlengrund 20, 46149 Oberhausen - Germany

t: +49 (0) 208 377 890-0 info@medical-econet.com f: +49 (0) 208 377 890-55 www.medical-econet.com facebook.com/medicaleconetgermany twitter.com/medicaleconet